

iData 25T 2-in-1 Smart Thermometer



➤ Non-contact industrial temperature measurement, multiple temperature measurement modes

- ◆ 0 ~ 6cm non-contact safety temperature measurement, providing more protection;
- ◆ Multiple temperature measurement modes, covering all detection objects;
- ◆ Intelligently sense ambient temperature, meet all temperature measurement requirements in 0 ~ 40 ° C environment;
- ◆ Built-in German Hyman thermopile sensor, accurate temperature measurement of ± 0.2 °C, temperature measurement time ≤ 1 S.

➤ Real-time reading of city code / health code / smart ID card / access card

- ◆ Real-time reading of city code / health code / ID card information, detection + identification + entry information in one step, improve operation efficiency;
- ◆ NFC-bound personnel access card, ID card + access card for quick verification and reading, meeting the requirements of access control management.

➤ Wi-Fi data transmission + camera / video recording, strengthen personnel information collection capabilities

- ◆ Wi-Fi data transmission, timely and efficient information transmission and upload;
- ◆ 8 MXP high-definition camera, take pictures / videos anytime, anywhere.

➤ Local/cloud storage & background system & big data platform

- ◆ Personnel information admission can choose multiple local / cloud storage schemes
- ◆ The backstage can inquire about the visits of people in and out of the enterprise / community / park in real time, and it can be displayed on a map.
- ◆ Big data platform AI intelligent processing, personnel information details are intelligently sorted and updated to ensure real-time + timely control measures are in place

➤ Long battery life+ long temperature measurement life

- ◆ Equipped with 2700mAh large capacity battery;
- ◆ Over 1 million times of temperature measurement button life, easily covering over one million people's temperature measurement needs.

➤ Enterprise-class configuration

- ◆ Enterprise-class Android OS;
- ◆ Quad-core 1.3GHz high-performance processor, 8GB ROM + 1GB RAM large-capacity storage;
- ◆ Enterprise-class Wi-Fi data communication;
- ◆ Supporting Bluetooth 4.2 LE communication;
- ◆ Slim design, weighing only 170g, easier to carry around and longtime use;
- ◆ Robust and reliable, meeting the drop standard of 1.5 meters high to the concrete floor.

System Configuration

CPU	Quad-core 1.3 GHz
Operating System	Android 8.1 Go
Memory	8GB ROM + 1GB RAM
Display	2.4 inch, 320*240 high resolution
Touch Panel	Capacitive touch panel
Camera	8 MXP autofocus camera in the back side
Keypad	21 front keys, 2 side keys, Power key, total 24 keys
Battery	3.8 V 2700mAh rechargeable lithium polymer battery
Charging	Supporting Type-C charging
Notification	Vibrator alerts/LED/Audio notification
Vibration Motor	Built-in programmable vibration motor
Sensor	G-Sensor
Intercom function	One-touch PTT call (optional)

Structural Parameters

Dimensions (LxWxD)	150mm x 54mm x 20mm
Weight	170g (battery included)

Communication Transmission

Wireless LAN	Wi-Fi 802.11 a/b/g/n (Dual-band Wi-Fi: 2.4G+5G)
Bluetooth	Bluetooth 4.2 LE

Operating Environment

Programming Language	Android Standard interface, Java, Secondary development SDK, API, DEMO
Operating Temp.	-20°C ~ 60°C (-4°F ~ 140°F)
Storage Temp.	-40°C ~ 60°C (-40°F ~ 140°F) battery included
Relative Humidity	0 ~ 95% (non-condensing)
Drop Specification	1.5-meter drops to concrete ground
Electrostatic Discharge	Conforms to ±15 kV air discharge, ±8 kV direct discharge

Temperature detection parameters

Measurement method	Non-contact / infrared
Measuring distance	0~6cm
Response Time	≤1S
Temperature Range	Normal mode: 32 ~ 42.9 °C Object mode: 0 ~ 100 °C
Resolution	0.01°C
Measurement accuracy	Normal mode 35 °C ~ 42 °C ± 0.2 °C, other ranges ± 0.3 °C Object mode ± 1.0 °C
Clinical reusability	±0.3°C
Operating environment	Temperature 0 ~ 40 °C, relative humidity ≤85% Rh, air pressure 60-110Kpa

NFC

Frequency	13.56 MHz
Reading Distance	Within 30 mm
Protocol	ISO14443A/14443B/15693

Input/output Ports

USB Port	1 (Type-C USB port)
----------	---------------------

Accessories

Standard	USB Cable, Hand strap
Optional	Power adapter



IDATA GLOBAL

Commercial HQ: Rm. 502, Sci.&Tech. Park Building, No.6, Keyuan Road,
Science and Technology Park, Shenzhen City, China

E-mail: sales@idataglobal.com

Website: www.idataglobal.com